

	XL750
Models	XL750 XL750
GENERAL	
Warranty	2 yrs
Service Intervals	12000 km
0 - 100 km/h (sec)	-
DIMENSIONS AND WEIGHTS	
Claimed KERB Weight	208
Length (mm)	2325
Width (mm)	838
Height (mm)	1450
Seat height (mm)	850/820 (STD Position/Optional Position)
Rake/Trail (°/mm)	111
Wheel Base	1560
DRIVE	
Drive	Chain
Front Suspension	Showa 43mm SFF-CA – 200mm travel
Rear Suspension	Monoshock damper, Pro-Link swingarm, 190mm travel
ENGINE	
Tank Capacity (I)	16.9
Starter	Electric
Engine Configuration	Liquid-cooled OHC 4stroke 8valve parallel twin with 270° crank and Unicam
Cylinders	2
Valves per Cylinder	4 Valves per Cylinder
Capacity	755cc
Power (KW)	67.5kW / 9,500rpm
Torque (NM)	75Nm @ 7,250rpm
Gearbox	6 speed Manual Transmission
SAFETY	
Brakes	ABS Type: 2 channel. Front: Dual 310mm x 4.5mm 'wave' discs with axial mounted, 2 piston calipers. Rear: Single 256mm x 6.0mm 'wave' disc is operated by a single-piston caliper.
STYLING	
Frame Material	Steel diamond
WHEELS	
Tyres Front	90/90-R21 M/C 54H
Tyres Rear	150/70-R18 M/C 70H
Wheels	Wheels Front: 21 inch (stainless steel) spoked wheels. Wheels Rear: 18 inch (stainless steel) spoked wheels
STANDARD AVAILABLE ACCESSORIES	
Luggage	-
Maintenance	-
Comfort	TFT 6.5-inch touch panel multi-information display
Utility	USB Type C (under the pillion seat). Auto Winker Cancel. Security System: HISS (Honda Intelligent Security System).

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.