

Mode's		XR190 CTP DK	
warranty 2 yrs Service Intervals 4000 km 0 - 100 km/k (sec)	Models		
Service Intervals 4000 km 0 - 100 km/t seed - DIMENSIONS AND WEIGHTS - Claimed KeRB Weight 123 Length (mm) 2075 Width (mm) 812 Height (mm) 2825 RakerTrail (*mm) 325 Mohed Base 1351 DIVE 150 DIVE Chain Prote Chain Font Suspension Tolescapic Fork, 161 mm Axie Travel Read Suspension Tolescapic Fork, 161 mm Axie Travel Read Suspension 12 Starter Beactive, 8 Back by Kick Englise Configuration Air Cooled Single Cylinder SOHC Cylinders 1 Values per Cylinder 4 Capacity 184 Power (KM) 114 (KW) Torque (MM) 5 Speed Manual SAFETY 240 mm Hydraulic Disc with Dual Piston Calliper STYLING 240 mm Hydraulic Disc with Dual Piston Calliper STYLING 3 Speed Manual STYLING 3 Speed Manual	GENERAL		
0.100 km/h (sec)	Warranty	2 yrs	
DIMENSIONS AND WEIGHTS	Service Intervals	4000 km	
Claimed KERB Weight	0 - 100 km/h (sec)	-	
Length (mm) 2075 Width (mm) 812 Height (mm) 825 Rake/Trail (*mm) 825 Rake/Trail (*mm)	DIMENSIONS AND WEIGHTS		
Width (mm) 812 Height (mm) 1124 Seat height (mm) 825 Rekel/Faul (*/mm) 1351 Wheel Base 1351 DRIVE The Chain Front Suspension Tolescopic Fork Inflam Axie Travel Rear Suspension Mono Shock Swing Arm. 151mm Axie Travel Rear Suspension Mono Shock Swing Arm. 151mm Axie Travel Rear Suspension 12 Starter Blectric & Back Up Kick English Air Cooled Single Cylinder SOHC Cylinders 1 Valves per Cylinder 4 Capacity 184 Power (KW) 11.4(KW) Grapue (NM) 15.7NM Grapue (NM) 15.7NM Grapue (NM) 240mm Hydraulic Disc with Dual Piston Calliper STYLING Trans Material STYLING Steel Twin Tube WHEELS Types Front Types Front 30,900 (19-inch) Types Front 30,900 (19-inch) Types Front 30,900 (19-inch) </td <td>Claimed KERB Weight</td> <td>123</td>	Claimed KERB Weight	123	
Height (mm) 825 Rake/Timel (fr/mm) 825 Rake/Timel (fr/mm) 1351 Wheel Base 1351 DRIVE Chain Prove Chain Front Suspension Telescopic Fork, 161mm Axie Travel Rear Suspension Mono Shock Swing Arm, 151mm Axie Travel ENGINE 12 Starter Electric & Back Up Kick Engine Configuration Air Cooled Single Cylinder SOHC Cylinders 1 Valves per Cylinder 4 Capacity 184 Power (KW) 11.4(KW) Tarque (MM) 15.7 NM Gearbox 5-Speed Manual SAFETY STYLING Frame Material \$tell Twin Tube WHEELS Tyrus Front Tyrus Front 9.090 (19-inch) Tyres Frant 9.090 (19-inch) Tyres Rear 11.090 (17-inch) Wheels Wire Spoke Wheel TANDARD AVAILABLE ACCESSORIES Maintenance Comfor	Length (mm)	2075	
Seet height (mm) 825 Rake/Trail (*/mm) 1351 Wheel Base 1351 DRIVE Drive Chain Formt Suspension Telescopic Fork, 161mm Axie Travel Rear Suspension Mono Shock Swing Arm, 151mm Axie Travel ENGINE Tork Capacity (f) 12 Starter Electric & Back Up Kick Engine Configuration Air Cooled Single Cylinder SOHC Valves per Cylinder 4 Capacity 1 Valves per Cylinder 4 Capacity 184 Power (KW) 11.4(KW) Torque (NM) 15.7MM Gearbox 5-Speed Manual STAFLING 5-Speed Manual STALING Frame Material Steet Twin Tube WHEELS Tyres Front 90/90 (19-inch) Tyres Front 90/90 (19-inch) Tyres Front 90/90 (19-inch) Tyres Front 90/90 (19-inch)	Width (mm)	812	
Rake/Irail ("mm) 1351 DRIVE Chain Prive Chain Front Suspension Telescopic Fork, 161mm Axle Travel Rear Suspension Mono Shock Swing Arm, 151mm Axle Travel ENGINE Intelescopic Fork, 161mm Axle Travel ENGINE Electric & Back Up Kick Engine Configuration Air Cooled Single Cylinder SOHC Cylinders 1 Cylinders 4 Capacity 184 Power (KW) 11.4(KW) Torque (IMM) 15.7MM Gearbox 5-Speed Manual SAFETY Street Erakes 240mm Hydraulic Disc with Dual Piston Calliper STYLING Steel Twin Tube WHEELS Tyres Front Tyres Front 90/90 (19-inch) Tyres Fro	Height (mm)	1124	
Wheel Base 1351 DRIVE Drive Chain Front Suspension Telescopic Fork, 161 mm Axle Travel Rear Suspension Mono Shock Swing Arm, 151 mm Axle Travel ENGINE ENGINE Engine Configuration 12 Starter Electric & Back Up Kick Engine Configuration Air Cooled Single Cylinder SOHC Cylinders 1 Valves per Cylinder 4 Capacity 184 Power (KW) 11.4(KW) Graque (NM) 15.7MM Gearbox 5-Speed Manual SAFETY Stream Brakes 240mm Hydraulic Disc with Dual Piston Calliper STYLING Steel Twin Tube WHEELS Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES Tyres Front 90/90 (19-inch)	Seat height (mm)	825	
DRIVE Drive Chain Front Suspension Telescopic Fork, 161mm Axie Travel Rear Suspension Mono Shock Swing Arm, 151mm Axie Travel ENGINE Tank Capacity (f) 12 Starter Electric & Back Up Kick Engine Configuration Air Cooled Single Cylinder SOHC Cylinders 1 Valves per Cylinder 4 Capacity 184 Power (KW) 11.4(KW) Torque (NM) 15.7MM Gearbox 5-Speed Manual SAFETY Brakes 240mm Hydraulic Disc with Dual Piston Calliper STYLING STYLING Tyres Front 90/90 (19-inch) Tyres Front 90/90 (19-inch) Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Mirrs Spoke Wheel STANDARD AVAILABLE ACCESSORIES Confort Luggage - Maintenance - Comfort	Rake/Trail (°/mm)		
Drive Chain Front Suspension Telescopic Fork, 161mm Axle Travel Rear Suspension Mono Shock Swing Arm, 151mm Axle Travel ENGINE Tank Capacity (I) 12 Starter Electric & Back Up Kick Engine Configuration Air Cooled Single Cylinder SOHC Cylinders 1 Valvies per Cylinder 4 Capacity 184 Power (KW) 11.4(KW) Torque (NM) 15.7NM Gearbox 5-Speed Manual SAFETY STYLING STYLING Steel Twin Tube WHEELS Tyres Front Material Steel Twin Tube WHEELS Tyres Front 90/90 (19-inch) 90/90 (19-inch) Tyres Front 90/90 (19-inch) 90/90 (19-inch) Tyres Front 90/90 (19-inch) 90/90 (19-inch) Tyres Front 90/90 (19-inch) 90/90 (19-inch) Wiesels 110/90 (17-inch) 90/90 (19-inch) Wiesels 90/90 (19-inch) 90/90 (19-inch) Wiesels 90/90 (19-inch)	Wheel Base	1351	
Front Suspension Telescopic Fork, 161mm Axie Travel Rear Suspension Mono Shock Swing Arm, 151mm Axie Travel FNGINE Tank Capacity (I) 12 Starter Flectric & Back Up Kick Engine Configuration Air Cooled Single Cylinder SOHC Cylinders 1 Capacity	DRIVE		
Rear Suspension Mono Shock Swing Arm, 151mm Axie Travel ENGINE Tank Capacity (I) 12 Starter Electric & Back Up Kick Engine Configuration Air Caoled Single Cylinder SOHC Cylinders 1 Valves per Cylinder 4 Capacity 184 Power (KW) 11.4(KW) Torque (NM) 5.5 peed Manual SAFETY System Manual SAFETY SYVLING Frame Material 240mm Hydraulic Disc with Dual Piston Calliper STYLING Steel Twin Tube WHEELS Tyres Front 90/90 (19-inch) Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES 4 Luggage - Maintenance - Comfort -	Drive	Chain	
ENGINE Tank Capacity (I) 12 Starter Electric & Back Up Kick Engine Configuration Air Cooled Single Cylinder SOHC Cylinders 1 Valves per Cylinder 4 Capacity 184 Power (KW) 11.4(KW) Torque (NM) 15.7NM Gearbox 5-Speed Manual SAFETY STYLING Frame Material Steel Twin Tube WHEELS Tyres Front Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES - Luggage - Maintenance - Comfort -	Front Suspension	Telescopic Fork, 161mm Axle Travel	
Tank Capacity (I) 12 Stater Electric & Back Up Kick Engine Configuration Air Cooled Single Cylinder SOHC Cylinders 1 Valves per Cylinder 4 Capacity 184 Power (KW) 11.4(KW) Torque (NM) 15.7NM Gearbox 5-Speed Manual SAFETY STYLING STYLING Steel Twin Tube WHEELS Tyres Front Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES Luggage Maintenance - Confort -	Rear Suspension	Mono Shock Swing Arm, 151mm Axle Travel	
Starter Electric & Back Up Kick Engine Configuration Air Cooled Single Cylinder SOHC Cylinders 1 Valves per Cylinder 4 Capacity 184 Power (KW) 11.4(KW) Torque (NM) 15.7NM Gearbox 5-Speed Manual SAFETY STYLING STYLING Steel Twin Tube WHEELS Tyres Front Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES 1 Luggage - Maintenance - Confort -	ENGINE		
Engine Configuration Air Cooled Single Cylinder SOHC Cylinders 1 Valves per Cylinder 4 Capacity 184 Power (KW) 11.4(KW) Torque (NM) 15.7NM Gearbox 5-Speed Manual SAFETY SAFETY Brakes 240mm Hydraulic Disc with Dual Piston Calliper STYLING Steel Twin Tube WHEELS Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES 1 Luggage - Maintenance - Confort -	Tank Capacity (I)	12	
Cylinders 1 Valves per Cylinder 4 Capacity 184 Power (KW) 11.4(KW) Torque (NM) 15.7NM Gearbox 5-Speed Manual SAFETY Brakes 240mm Hydraulic Disc with Dual Piston Calliper STYLING Trame Material Steel Twin Tube WHEELS Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES Luggage - Maintenance - Confort -	Starter	Electric & Back Up Kick	
Valves per Cylinder 4 Capacity 184 Power (KW) 11.4(KW) Torque (NM) 15.7NM Gearbox 5-Speed Manual SAFETY Brakes 240mm Hydraulic Disc with Dual Piston Calliper STYLING Frame Material Steel Twin Tube WHEELS Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES Luggage - Maintenance - Confort -	Engine Configuration	Air Cooled Single Cylinder SOHC	
Capacity 184 Power (KW) 11.4(KW) Torque (NM) 15.7NM Gearbox 5-Speed Manual SAFETY	Cylinders	1	
Power (KW) 11.4(KW) Torque (NM) 15.7NM Gearbox 5-Speed Manual SAFETY Brakes 240mm Hydraulic Disc with Dual Piston Calliper STYLING Frame Material Steel Twin Tube WHEELS Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES Luggage - Maintenance - Confort -	Valves per Cylinder	4	
Torque (NM) 15.7NM Gearbox 5-Speed Manual SAFETY Brakes 240mm Hydraulic Disc with Dual Piston Calliper STYLING Frame Material Steel Twin Tube WHEELS Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES - Luggage - Maintenance - Comfort -	Capacity	184	
Gearbox5-Speed ManualSAFETYBrakes240mm Hydraulic Disc with Dual Piston CalliperSTYLINGFrame MaterialSteel Twin TubeWHEELSTyres Front90/90 (19-inch)Tyres Rear110/90 (17-inch)WheelsWire Spoke WheelSTANDARD AVAILABLE ACCESSORIESLuggage-Maintenance-Comfort-	Power (KW)	11.4(KW)	
SAFETY Brakes 240mm Hydraulic Disc with Dual Piston Calliper STYLING Frame Material Steel Twin Tube WHEELS Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES Luggage Maintenance Comfort Comfort Maintenance Comfort	Torque (NM)	15.7NM	
Brakes 240mm Hydraulic Disc with Dual Piston Calliper STYLING Frame Material Steel Twin Tube WHEELS Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES Luggage Maintenance - Comfort Comfort Marrian Hydraulic Disc with Dual Piston Calliper 240mm Hydraulic Disc with Dual Piston Calliper Allows All	Gearbox	5-Speed Manual	
STYLING Frame Material Steel Twin Tube WHEELS Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES Luggage Maintenance Comfort	SAFETY		
Frame Material Steel Twin Tube WHEELS Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES Luggage Maintenance Comfort	Brakes	240mm Hydraulic Disc with Dual Piston Calliper	
WHEELS Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES Luggage Maintenance Comfort	STYLING		
Tyres Front 90/90 (19-inch) Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES Luggage Maintenance Comfort	Frame Material	Steel Twin Tube	
Tyres Rear 110/90 (17-inch) Wheels Wire Spoke Wheel STANDARD AVAILABLE ACCESSORIES Luggage - Maintenance - Comfort -	WHEELS		
Wheels STANDARD AVAILABLE ACCESSORIES Luggage Lugnace Maintenance Comfort Wire Spoke Wheel	Tyres Front	90/90 (19-inch)	
STANDARD AVAILABLE ACCESSORIES Luggage	Tyres Rear	110/90 (17-inch)	
Luggage -	Wheels	Wire Spoke Wheel	
Maintenance - Comfort -	STANDARD AVAILABLE ACCESSORIES		
Maintenance - Comfort -	Luggage	-	
		-	
Utility -	Comfort	-	
	Utility	-	

DISCLAIMER

Whilst Honda Motor Southern Africa takes reasonable care to ensure the accuracy and completeness of any data or information provided by it on this web site, any person accessing this web site agrees that by so accessing this web site that Honda Motor Southern Africa, its officers, employees and agents do not accept any liability of whatsoever nature for any direct, incidental or consequential loss or damage of any kind or nature, howsoever arising from the use of or reliance on any such data or information Please note all prices featured on the Honda Motor Southern Africa web site are manufacturer recommended prices and indicative only.